

 Issue Date:
 16.01.2013
 Version: 2.1
 SDS No.: 000010021714

 Last revised date:
 30.03.2020
 1/13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Carbon dioxide

Trade name: BIOGON® C (E290), Carbon dioxide 2.8 Industrial, Carbon dioxide 4.0

ANAEROBE, Carbon dioxide 4.0 HiQ, Carbon dioxide 4.5 HiQ, Carbon dioxide 4.5 Instrument, Carbon dioxide 4.5 Laser, Carbon dioxide 4.8 Laboratory, Carbon dioxide 5.2 Scientific, Carbon dioxide 5.3, Carbon dioxide 5.6, Carbon dioxide VERISEQ® Process, Carbon dioxide VERISEQ® Research; Carbon

dioxide, medical device grade

Other Name: R744

Additional identification

Chemical name: Carbon dioxide

Chemical formula: CO2 INDEX No. -

CAS-No. 124-38-9 EC No. 204-696-9

REACH Registration No. Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted

from registration.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use. Aerosol

propellant. Balance gas for mixtures. Beverage applications. Biocidal uses. Blanketing gas. Blast cleaning. Calibration gas. Carrier gas. Chemical synthesis. Combustion, melting and cutting processes. Cooling applications. Fire suppressant gas. Food freezing. Food packaging gas. Freezing, Cooling and heat transfer. Inerting gas. Inflation systems. Laboratory use. Laser gas. Plant growth promoter. Pressure head gas, operational assist gas in pressure systems. Process gas. Purge gas. Refrigerant. Solvent for extraction. Special

effects (entertainment). Test gas.

Consumer use. Propellant gas. Shielding gas in gas welding.

It is the responsibility of the end user to ensure that the product as supplied is

suitable for its intended use.

Uses advised against Industrial or technical grade is unsuitable for medical and/or food

applications or inhalation.

1.3 Details of the supplier of the safety data sheet

Supplier

Linde Gas A/S
Lautruphøj 2-6
Telephone: +4532836600

2750 Ballerup Denmark

E-mail: sds.ren@linde.com

SDS_DK - 000010021714



SAFETY DATA SHEET Carbon dioxide

 Issue Date:
 16.01.2013
 Version: 2.1
 SDS No.: 000010021714

 Last revised date:
 30.03.2020
 2/13

1.4 Emergency telephone number: Poison control hotline: tel. +45 82 12 12 12

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure Liquefied gas H280: Contains gas under pressure; may explode if

heated.

2.2 Label Elements



Signal Words: Warning

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.

Precautionary Statements

Prevention: None.

Response: None.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

Supplemental label information

EIGA-As: Asphyxiant in high concentrations.

2.3 Other hazards: Contact with evaporating liquid may cause frostbite or freezing of skin.



Issue Date: 16.01.2013 Version: 2.1 SDS No.: 000010021714
Last revised date: 30.03.2020 3/13

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name Carbon dioxide

INDEX No.:

CAS-No.: 124-38-9 EC No.: 204-696-9

REACH Registration No.: Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from

registration.

Purity: 100%

The purity of the substance in this section is used for classification only, and does

not represent the actual purity of the substance as supplied, for which other

documentation should be consulted.

Trade name: BIOGON® C (E290), Carbon dioxide 2.8 Industrial, Carbon dioxide 4.0 ANAEROBE,

Carbon dioxide 4.0 HiQ, Carbon dioxide 4.5 HiQ, Carbon dioxide 4.5 Instrument, Carbon dioxide 4.5 Laser, Carbon dioxide 4.8 Laboratory, Carbon dioxide 5.2 Scientific, Carbon dioxide 5.3, Carbon dioxide 5.6, Carbon dioxide VERISEQ® Process, Carbon dioxide VERISEQ® Research; Carbon dioxide, medical device

grade

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Low concentrations of CO2 cause increased respiration and headache.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy

to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available,

flush an additional 15 minutes.

Skin Contact: Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and

effects, both acute and

delayed:

Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to

rapid evaporative cooling.



Issue Date: 16.01.2013 Version: 2.1 SDS No.: 000010021714
Last revised date: 30.03.2020 4/13

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to

rapid evaporative cooling.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate

medical advice/attention.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Material will not burn. In case of fire in the surroundings: use appropriate

extinguishing agent.

Unsuitable extinguishing

media:

None.

5.2 Special hazards arising from the

substance or mixture:

None.

Hazardous Combustion Products: None.

5.3 Advice for firefighters

Special fire fighting

procedures:

In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate

the source of the fire or let it burn out.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained opencircuit compressed air breathing apparatus with full face mask - Requirements,

testing, marking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements,

testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so.

SDS_DK - 000010021714



Issue Date: 16.01.2013 Version: 2.1 SDS No.: 000010021714
Last revised date: 30.03.2020 5/13

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation.

6.4 Reference to other sections: Refer to sections 8 and 13.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eq. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place. Depressurisation of liquid CO2 below approximately 5 bar can create solid CO2 which may block protective devices, pipework and create dry-ice within containers. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide.

7.2 Conditions for safe storage, including any incompatibilities:

Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material

7.3 Specific end use(s):

None.



Issue Date: 16.01.2013 Version: 2.1 SDS No.: 000010021714
Last revised date: 30.03.2020 6/13

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Туре	Exposure Limit Values		Source
Carbon dioxide	TWA	5.000 ppm	9.000 mg/m3	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU (12 2009)
	GV	5.000 ppm	9.000 mg/m3	Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3 (12 2011)

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product. CO2 detectors should be used when CO2 may be released.

Individual protection measures, such as personal protective equipment

General information: A risk assessment should be conducted and documented in each work area to

assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task

being performed and the risks involved.

Eye/face protection: Safety eyewear, goggles or face-shield to EN166 should be used to avoid

exposure to liquid splashes. Wear eye protection to EN 166 when using gases.

Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection: Wear working gloves while handling containers

Guideline: EN 388 Protective gloves against mechanical risks.

Body protection: No special precautions.

Other: Wear safety shoes while handling containers

Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection: Not required.



 Issue Date:
 16.01.2013
 Version: 2.1
 SDS No.: 000010021714

 Last revised date:
 30.03.2020
 7/13

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Specific risk management measures are not required beyond good industrial

hygiene and safety procedures. Do not eat, drink or smoke when using the

product.

Environmental exposure

controls:

For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Gas

Form: Liquefied gas
Color: Colorless
Odor: Odorless

Odor Threshold: Odor threshold is subjective and is inadequate to warn of over

exposure.

pH: 3,2 - 3,7 The pH of saturated CO2 solutions varies from 3.7 at

101 kPa (1 atm) to 3.2 at 2370 kPa (23.4 atm)

Melting Point: -56,6 °C Boiling Point: -78,5 °C Sublimation Point: -78,5 °C Critical Temp. (°C): 31,0 °C

Flash Point: Not applicable to gases and gas mixtures. **Evaporation Rate:** Not applicable to gases and gas mixtures.

Flammability (solid, gas): This product is not flammable.

Flammability Limit - Upper (%):

Not applicable.

Not applicable.

Not applicable.

Vapor pressure:

45,1 bar (10 °C)

Vapor density (air=1):

1,522 (21 °C)

Relative density:

1,512 (-56,6 °C)

Solubility(ies)

Solubility in Water: 2,900 mg/l (25 °C)

Partition coefficient (n-octanol/water): 0,83

Autoignition Temperature:Not applicable.Decomposition Temperature:Not known.

Viscosity

Kinematic viscosity:No data available.Dynamic viscosity:0,07 mPa.s (20 °C)Explosive properties:Not applicable.



SAFETY DATA SHEET Carbon dioxide

Issue Date: 16.01.2013 Version: 2.1 SDS No.: 000010021714
Last revised date: 30.03.2020 8/13

Oxidizing properties: Not applicable.

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined

spaces, particularly at or below ground level.

Molecular weight: 44,01 g/mol (CO2)

SECTION 10: Stability and reactivity

10.1 Reactivity: No reactivity hazard other than the effects described in sub-section below.

10.2 Chemical Stability: Stable under normal conditions.

10.3 Possibility of hazardous

reactions:

None.

10.4 Conditions to avoid: None.

10.5 Incompatible Materials: No reaction with any common materials in dry or wet conditions.

10.6 Hazardous Decomposition

Products:

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

General information: In high concentrations may cause rapid circulatory deterioration even at normal

levels of oxygen concentration. Symptoms are headache, nausea and vomiting,

which may lead to unconsciousness and even death.

11.1 Information on toxicological effects

Acute toxicity - Oral

Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal

Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation

Product Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation

Product Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation

Product Based on available data, the classification criteria are not met.



SAFETY DATA SHEET Carbon dioxide

Issue Date: 16.01.2013 Version: 2.1 SDS No.: 000010021714
Last revised date: 30.03.2020 9/13

Respiratory or Skin Sensitization

Product Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product Based on available data, the classification criteria are not met.

Carcinogenicity

Product Based on available data, the classification criteria are not met.

Reproductive toxicity

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product No ecological damage caused by this product.

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures...

12.3 Bioaccumulative potential

Product The subject product is expected to biodegrade and is not expected to persist for

long periods in an aquatic environment.

12.4 Mobility in soil

Product Because of its high volatility, the product is unlikely to cause ground or water

pollution.

12.5 Results of PBT and vPvB

assessment

Product Not classified as PBT or vPvB.

12.6 Other adverse effects: No ecological damage caused by this product.



SAFETY DATA SHEET Carbon dioxide

 Issue Date:
 16.01.2013
 Version: 2.1
 SDS No.: 000010021714

 Last revised date:
 30.03.2020
 10/13

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Do not discharge into any place where its accumulation could be dangerous. Vent

to atmosphere in a well ventilated place.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to

national, state, or local laws.

European Waste Codes

Container: 16 05 05: Gases in pressure containers other than those mentioned in 16 05

04.

SECTION 14: Transport information

ADR

14.1 UN Number: UN 1013

14.2 UN Proper Shipping Name: CARBON DIOXIDE

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.2
Hazard No. (ADR): 20
Tunnel restriction code: (C/E)

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user: –

RID

14.1 UN Number: UN 1013

14.2 UN Proper Shipping Name CARBON DIOXIDE

14.3 Transport Hazard Class(es)

Class: 2 Label(s): 2.2

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user: –



Issue Date: 16.01.2013 Version: 2.1 SDS No.: 000010021714
Last revised date: 30.03.2020 11/13

IMDG

14.1 UN Number: UN 1013

14.2 UN Proper Shipping Name: CARBON DIOXIDE

14.3 Transport Hazard Class(es)

 Class:
 2.2

 Label(s):
 2.2

 EmS No.:
 F-C, S-V

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user: –

IATA

14.1 UN Number: UN 1013

14.2 Proper Shipping Name: Carbon dioxide

14.3 Transport Hazard Class(es):

 Class:
 2.2

 Label(s):
 2.2

14.4 Packing Group: –

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

Other information

Passenger and cargo aircraft: Allowed. Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from

the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure

adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.: Not applicable



SAFETY DATA SHEET Carbon dioxide

 Issue Date:
 16.01.2013
 Version: 2.1
 SDS No.: 000010021714

 Last revised date:
 30.03.2020
 12/13

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include

but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)

(http://www.atsdr.cdc.gov/).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling

auide.

International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and

oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database

Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network

TOXNET (http://toxnet.nlm.nih.gov/index.html)

Threshold Limit Values (TLV) from the American Conference of Governmental

Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H280 Contains gas under pressure; may explode if heated.

Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Liq. Gas, H280



SAFETY DATA SHEET Carbon dioxide

 Issue Date:
 16.01.2013
 Version: 2.1
 SDS No.: 000010021714

 Last revised date:
 30.03.2020
 13/13

Other information: Before using this product in any new process or experiment, a thorough material

compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting

from its use can be accepted.

Last revised date: 30.03.2020

Disclaimer: This information is provided without warranty. The information is believed to be

correct. This information should be used to make an independent determination of

the methods to safeguard workers and the environment.