

TL4 Leak detecting spray

Issue Date:
Last revised date:

13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 1/21

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Product name: TL4 Leak detecting spray Trade name: TL4 LÆKSØGNINGSSPRAY 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses: Consumer use. Industrial and professional. Perform risk assessment prior to use. Uses advised against Contact supplier for more information on uses. 1.3 Details of the supplier of the safety data sheet Supplier Linde Gas A/S Telephone: +4532836600 Lautruphøj 2-6 2750 Ballerup E-mail: sds.ren@linde.com 1.4 Emergency telephone number: Poison control hotline: tel. +45 82 12 12 12 SECTION 2: Hazards identification 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards Aerosols	Category 3	H229: Pressurized container: May burst if heated.
Health Hazards Serious eye irritation	Category 2	H319: Causes serious eye irritation.

2.2 Label Elements



	1	SAFETY DATA SHEET			
TL4 Leak detecting spray					
Issue Date: Last revised date:	13.10.2020 23.10.2020	Version: 1.0	SDS No.: 000010059150 2/21		
Signal Word:	Warning				
-	C C				
Hazard Statement(s		surized container: May burst if he ses serious eye irritation.	eated.		
Precautionary State General	ments None.				
Prevention:	ignition sou P251: Do n P264: Wasl	o away from heat, hot surfaces, s urces. No smoking. lot pierce or burn, even after use. h hands thoroughly after handlin Ir protective gloves/protective cl	g.		
Response:	P337+P313	3: If eye irritation persists: Get me	edical advice/attention.		
Storage:	P410+P412 50 °C/122	5	xpose to temperatures exceeding		
Disposal	disposal fa	ose of contents/container to an a cility in accordance with applicat aracteristics at time of disposal.			
Supplemental information	EUH208: Co reaction	ontains1,2-Benzisothiazol-3(2H)-on	ne. May produce an allergic		
2.3 Other hazards	None.				

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
2-Amino-2- methylpropanol	C4H11NO	0,99%	124-68-5	01- 2119475788- 16	-	#



SAFETY DATA SHEET TL4 Leak detecting spray

Issue Date: Last revised date: 13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 3/21

(Z)-N-Methyl-N-(1- oxo-9- octadecenyl)glycine	C21H39NO3	2,49%	110-25-8	Not available.	-	
Amines, C12-14 (even numbered)- alkyldimethyl, N- oxides	CnH(2n+3)NO , where n=14/16	2.499PPM	308062-28-4	01- 2119490061- 47	-	
4,4- Dimethyloxazolidine	C5H11NO	999PPM	51200-87-4	01- 2120794002- 61	-	
2-Aminobutan-1-ol	C4H11NO	999PPM	96-20-8	01- 2119492338- 28	-	
1,2-Benzisothiazol- 3(2H)-one	C7H5NOS	249PPM	2634-33-5	01- 2120761540- 60	-	
Water	H2O	96,0454%	7732-18-5	Not available.	-	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Classification		Notes
2-Amino-2-methylpropanol	CLP:	Skin Irrit. 2;H315, Eye Irrit. 2;H319, Aquatic Chronic 3;H412	
(Z)-N-Methyl-N-(1-oxo-9- octadecenyl)glycine	CLP:	Aquatic Acute 1;, Skin Irrit. 2;H315, Eye Dam. 1;H318, Acute Tox. 4;H332, Aquatic Acute 1;H400	
Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	CLP:	Acute Tox. 4;H302, Skin Irrit. 2;H315, Eye Dam. 1;H318, Aquatic Acute 1;H400, Aquatic Chronic 2;H411	
4,4-Dimethyloxazolidine	CLP:	Acute Tox. 4;, Flam. Liq. 3;H226, Acute Tox. 4;H302, Acute Tox. 3;H331, Skin Irrit. 2;H315, Eye Dam. 1;H318	
2-Aminobutan-1-ol	CLP:	Skin Sens. 1;, Acute Tox. 4;H302, Skin Corr. 1B;H314, Eye Dam. 1;H318, Aquatic Acute 1;H400	
1,2-Benzisothiazol-3(2H)-one	CLP:	Acute Tox. 4;H302, Skin Irrit. 2;H315, Eye Dam. 1;H318, Skin Sens. 1;H317, Aquatic Acute 1;H400, Aquatic Chronic 2;H411	
Water	CLP:	none	

CLP: Regulation No. 1272/2008.

The full text for all H-statements is displayed in section 16.



TL4 Leak detecting spray

Issue Date: Last revised date: 13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 4/21

SECTION 4: First aid measures	
General:	Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
4.1 Description of first aid measures	
Inhalation:	Move the exposed person to fresh air at once. If breathing stops, provide artificial respiration. Symptoms may include: Dizziness. Nausea, vomiting.
Eye contact:	Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.
Ingestion:	Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately.
4.2 Most important symptoms and effects, both acute and delayed:	Irritating to eyes, respiratory system and skin.
4.3 Indication of any immediate me	dical attention and special treatment needed
Hazards:	Irritating to eyes, respiratory system and skin.
Treatment:	Do not give direct mouth-to-mouth resuscitation if swallowed. To protect rescuer, use air-viva, oxy-viva or one-way mask. Resuscitate in a well-ventilated area. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Treat with a corticosteroid spray as soon as possible after inhalation. Get immediate medical advice/attention.
SECTION 5: Firefighting measures	
General Fire Hazards:	Heat may cause the containers to explode.
5.1 Extinguishing media Suitable extinguishing media:	Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam. Carbon Dioxide.



TL4 Leak detecting spray

Issue Date:	13.10.2020	Version: 1.0	SDS No.: 000010059150
Last revised date:	23.10.2020		5/21

Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
5.2 Special hazards arising from the substance or mixture:	Fire or excessive heat may produce hazardous decomposition products.
5.3 Advice for firefighters Special fire fighting procedures:	In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.
Special protective equipment for fire-fighters:	Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus. Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	Evacuate area. Provide adequate ventilation. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
6.2 Environmental Precautions:	Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.
6.3 Methods and material for containment and cleaning up:	Provide adequate ventilation. Wash contaminated equipment or sites of leaks with copious quantities of water.
6.4 Reference to other sections:	Refer to sections 8 and 13.



TL4 Leak detecting spray

Issue Date: Last revised date: 13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 6/21

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Keep container below 50°C in a well ventilated place. Avoid suckback of water, acid and alkalis. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
7.2 Conditions for safe storage, including any incompatibilities:	Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.
7.3 Specific end use(s):	None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
2-Amino-2- methylpropanol	GV	3 ppm	Denmark. Danish List of Organic Solvents, Danish Labor Inspectorate (08 2007)



TL4 Leak detecting spray

Issue Date: Last revised date: 13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 7/21

DNEL-Values

Critical component	Туре	Value	Remarks
(Z)-N-Methyl-N-(1-oxo-9-	Workers - Inhalation,	18 mg/m3	Acute toxicity
octadecenyl)glycine	Systemic, short-term	5,	,
	Workers - Inhalation,	0,2 mg/m3	Repeated dose toxicity
	Systemic, long-term		
	Workers - Dermal, Systemic,	10 mg/kg	Repeated dose toxicity
	long-term	bw/day	
	Workers - Inhalation, Local,	0,01	Repeated dose toxicity
	long-term	mg/m3	
	Workers - Inhalation, Local,	18 mg/m3	Acute toxicity
	short-term		
	Workers - Eyes, Local effect		No data available

PNEC-Values

•				
	Critical component	Туре	Value	Remarks



TL4 Leak detecting spray

Issue Date: Last revised date: 13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 8/21

2-Amino-2-methylpropanol	Aquatic (freshwater)	0,188 mg/l	-
2-Amino-2-methylpropanol	Sewage treatment plant	10 mg/l	-
2-Amino-2-methylpropanol	Aquatic (marine water)	0,019 mg/l	-
2-Amino-2-methylpropanol	Sediment (marine water)	0,071 mg/kg	-
2-Amino-2-methylpropanol	Soil	0,03 mg/kg	-
2-Amino-2-methylpropanol	Sediment (freshwater)	0,71 mg/kg	-
(Z)-N-Methyl-N-(1-oxo-9- octadecenyl)glycine	Aquatic (intermit. releases)	4,3 µg/l	-
(Z)-N-Methyl-N-(1-oxo-9- octadecenyl)glycine	Aquatic (marine water)	0,043 µg/l	-
(Z)-N-Methyl-N-(1-oxo-9- octadecenyl)glycine	Sewage treatment plant	13 mg/l	-
(Z)-N-Methyl-N-(1-oxo-9- octadecenyl)glycine	Aquatic (freshwater)	0,43 µg/l	-
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	Aquatic (marine water)	0,003 mg/l	-
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	Soil	1,02 mg/kg	-
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	Sediment (marine water)	0,524 mg/kg	-
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	Aquatic (freshwater)	0,034 mg/l	-
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	Sediment (freshwater)	5,24 mg/kg	-



TL4 Leak detecting spray

Issue Date: Last revised date: 13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 9/21

Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	Predator	11,1 mg/kg	Oral
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	Sewage treatment plant	24 mg/l	-
2-Aminobutan-1-ol	Soil	0,18 µg/kg	-
2-Aminobutan-1-ol	Sewage treatment plant	10 mg/l	-
2-Aminobutan-1-ol	Sediment (freshwater)	3,59 µg/kg	-
2-Aminobutan-1-ol	Sediment (marine water)	0,359 µg/kg	-
2-Aminobutan-1-ol	Aquatic (marine water)	0 mg/l	-
2-Aminobutan-1-ol	Aquatic (intermit. releases)	0,009 mg/l	-
2-Aminobutan-1-ol	Aquatic (freshwater)	0,001 mg/l	-

8.2 Exposure controls

Appropriate engineering controls: Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Do not eat, drink or smoke when using the product.

Individual protection measures, such as personal protective equipment

General information:A risk assessment should be conducted and documented in each work area to
assess the risks related to the use of the product and to select the PPE that
matches the relevant risk. The following recommendations should be considered.
Keep self contained breathing apparatus readily available for emergency use.
Keep suitable chemically resistant protective clothing readily available for
emergency use. Personal protective equipment for the body should be selected
based on the task being performed and the risks involved. For waste disposal, see
section 13 of the SDS. Protect eyes, face and skin from contact with product.



TI A Look dotoctiv

	TL4 Leak detecting spray				
Issue Date: Last revised date:	13.10.2020 23.10.2020	Version: 1.0	SDS No.: 000010059150 10/21		
Eye/face protection:	exposure to	wear, goggles or face-shield to EN o liquid splashes. Wear eye protect EN 166 Personal Eye Protection.			
Skin protection Hand Protection:	Additional Guideline: organisms. Additional be worn at	EN 388 Protective gloves against m Information: Wear working gloves EN 374-1/2/3 Protective gloves a Information: Chemically resistant g all times when handling chemical his is necessary.	while handling containers gainst chemicals and micro- Jloves complying with EN 374 should		
Body protection:	No special	precautions.			
Other:		y shoes while handling containers ISO 20345 Personal protective equ	ipment - Safety footwear.		
Respiratory Protection:	assessmen documents selection o anticipatec	for methods for the determination	nical agents and national guidance n of hazardous substances. The e (RPD) must be based on known or		
Thermal hazards:	No precaut	ionary measures are necessary.			
Hygiene measures:	required be		ic risk management measures are not safety procedures. Do not eat, drink		
Environmental exposure controls:	For waste o	lisposal, see section 13 of the SDS.			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	
Physical state:	liquid
Form:	liquid
Color:	H2O: Colorless
Odor:	H2O: Odorless
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over

SDS_DK - 000010059150



SAFETY DATA SHEET TL4 Leak detecting spray

Issue Date: Last revised date: 13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 11/21

	exposure.
pH:	7,76
Freezing point:	No data available.
Boiling Point:	No data available.
Sublimation Point:	Not applicable.
Critical Temp. (°C):	No data available.
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	This product is not flammable.
Flammability Limit - Upper (%):	Not applicable.
Flammability Limit - Lower (%):	Not applicable.
Vapor pressure:	No reliable data available.
Vapor density (air=1):	No data available.
Relative density:	0,999 (20 °C)
Solubility(ies)	
Solubility in Water:	Soluble
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.
9.2 Other information:	None.
VOC Content:	EC Directive 1999/13: 9,89 g/l ~0,99 % (calculated) EC Directive 2004/42: 36,76 g/l ~3,68 % (calculated)

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	No data available.



TL4 Leak detecting spray

Issue Date:	13.10.2020	Version: 1.0	SDS No.: 000010059150
Last revised date:	23.10.2020		12/21

10.4 Conditions to avoid:	No data available.
10.5 Incompatible Materials:	No data available.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
SECTION 11: Toxicological information	tion
General information:	None.
11.1 Information on toxicological eff	ects
Acute toxicity - Oral Product	ATEmix: > 2.000 mg/kg Based on available data, the classification criteria are not met.
Component Information 2-Amino-2- methylpropanol	LD 50 (Rat): 2.900 mg/kg Remarks: Experimental result, Key study
(Z)-N-Methyl-N-(1-oxo- 9-octadecenyl)glycine	LD 50 (Rat): > 5.000 mg/kg Remarks: Experimental result, Key study
Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	LD 50 (Rat): 1.064 mg/kg Remarks: Experimental result, Key study
4,4-Dimethyloxazolidine	LD 50 (Rat): 956 mg/kg
2-Aminobutan-1-ol	LD 50 (Rat): 1.800 mg/kg Remarks: Experimental result, Key study
1,2-Benzisothiazol- 3(2H)-one	LD 50 (Rat): 490 mg/kg
Acute toxicity - Dermal Product	ATEmix: > 2.000 mg/kg Based on available data, the classification criteria are not met.



TL4 Leak detecting spray

Issue Date:	
Last revised date:	

13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 13/21

Component Information 2-Amino-2- methylpropanol	LD 50 (Rabbit): > 2.000 mg/kg Remarks: Experimental result, Key study
Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	LD 50 (Rat): > 2.000 mg/kg Remarks: Read-across from supporting substance (structural analogue or surrogate), Key study
4,4-Dimethyloxazolidine	LD 50 (Rabbit): 2.000 mg/kg
2-Aminobutan-1-ol	Remarks: Irritating to skin.
1,2-Benzisothiazol- 3(2H)-one	LD 50 (Rat): 2.000 mg/kg
Acute toxicity - Inhalation Product	Based on available data, the classification criteria are not met.
Component Information Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	Remarks: Not classified for acute toxicity based on available data.
4,4-Dimethyloxazolidine	LC 50 (Rat, 4 h): 11,6 mg/l
2-Aminobutan-1-ol	Remarks: Not classified for acute toxicity based on available data.
1,2-Benzisothiazol- 3(2H)-one	Remarks: Not classified for acute toxicity based on available data.
Repeated dose toxicity Component Information 2-Amino-2- methylpropanol	LOAEL (Rat(Female, Male), Oral, 13 Weeks): < 500 mg/kg Oral Experimental result, Supporting study
(Z)-N-Methyl-N-(1-oxo- 9-octadecenyl)glycine	NOAEL (Rat(Male), Inhalation): > 0,06 mg/l Inhalation Experimental result, Key study



TL4 Leak detecting spray

Issue Date:	13.10.2020	Version: 1.0	SDS No.: 000010059150
Last revised date:	23.10.2020		14/21

	Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	NOAEL (Rat(Female, Male), Oral, 13 Weeks): 88 mg/kg Oral Experimental result, Supporting study
	2-Aminobutan-1-ol	NOAEL (Rat(Female, Male), Oral, 33 - 64 d): 10 mg/kg Oral Experimental result, Key study
	Corrosion/Irritation oduct	Based on available data, the classification criteria are not met.
Co	mponent Information (Z)-N-Methyl-N-(1-oxo- 9-octadecenyl)glycine	in vivo (Rabbit): Irritating Experimental result, Key study
	4,4-Dimethyloxazolidine	Irritating to skin.
	1,2-Benzisothiazol- 3(2H)-one	Irritating to skin.
	us Eye Damage/Eye Irritati oduct	on Causes serious eye irritation.
Co	mponent Information 2-Amino-2- methylpropanol	in vivo (Rabbit, 48 hrs): Category 1EU
	Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	in vivo (Rabbit, 1 d): Category 1EU
	4,4-Dimethyloxazolidine	Irritating to eyes.
	1,2-Benzisothiazol- 3(2H)-one	Irritating to eyes.

Respiratory or Skin Sensitization Product

Based on available data, the classification criteria are not met.



TL4 Leak detecting spray

Issue Date: Last revised date: 13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 15/21

Component Information 1,2-Benzisothiazol- 3(2H)-one	May cause sensitization.	
Germ Cell Mutagenicity Product	Based on available data, the classification criteria are not met.	
Carcinogenicity Product	Based on available data, the classification criteria are not met.	
Reproductive toxicity Product	Based on available data, the classification criteria are not met.	
Specific Target Organ Toxicity - Single ExposureProductBased on available data, the classification criteria are not met.		
Specific Target Organ Toxicity - Repeated ExposureProductBased on available data, the classification criteria are not met.		
Aspiration Hazard Product	No data available.	
TION 12. Ecological information		

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity Product	No ecological damage caused by this product.
Acute toxicity - Fish Component Information 2-Amino-2-methylpropanol	LC 50 (Lepomis macrochirus, 48 h): 220 mg/l (Static) Remarks: Experimental result, Key study
(Z)-N-Methyl-N-(1-oxo-9- octadecenyl)glycine	NOAEL (Leuciscus idus, 96 h): 6,81 mg/l (Static) Remarks: Experimental result, Key study
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	LC 50 (Pimephales promelas, 96 h): 2,67 mg/l (Static) Remarks: Experimental result, Key study



TL4 Leak detecting spray

Issue Date:	
Last revised date:	

13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 16/21

Acute toxicity - Aquatic Invertet Component Information	prates
2-Amino-2-methylpropanol	LC 50 (Crangon crangon, 48 h): 179 mg/l (semi-static) Remarks: Experimental result, Key study
(Z)-N-Methyl-N-(1-oxo-9- octadecenyl)glycine	NOAEL (Daphnia magna, 48 h): 0,38 mg/l (Static) Remarks: Experimental result, Key study
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	EC 50 (Daphnia magna, 48 h): 10,4 mg/l (Static) Remarks: Experimental result, Key study
2-Aminobutan-1-ol	EC 50 (Daphnia magna, 48 h): 115 mg/l (Static) Remarks: Experimental result, Key study
Chronic Toxicity - Aquatic Invert	ebrates
Component Information Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	LC 50 (Daphnia magna, 21 d): 0,96 mg/l (flow-through) Experimental result, Key study
12.2 Persistence and Degradability Product	Not applicable to gases and gas mixtures
Biodegradation	
Component Information 2-Amino-2-methylpropanol	89,3 % (28 d) Detected in water. Experimental result, Key study
(Z)-N-Methyl-N-(1-oxo-9- octadecenyl)glycine	85,2 % Detected in water. Experimental result, Key study
Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	93 % (4 Weeks) Detected in water. Experimental result, Supporting study
2-Aminobutan-1-ol	100 % (28 d) Detected in water. Experimental result, Key study



TL4 Leak detecting spray

Issue Date:	
Last revised date:	

13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 17/21

12.3 Bioaccumulative potential Product	The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.	
Bioconcentration Factor (BCF) Component Information 2-Amino-2-methylpropanol	Leuciscus idus, Bioconcentration Factor (BCF): < 1 Aquatic sediment Experimental result, Supporting study	
12.4 Mobility in soil Product	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
12.5 Results of PBT and vPvB assessment Product	Not classified as PBT or vPvB.	
12.6 Other adverse effects:	No ecological damage caused by this product.	
SECTION 13: Disposal considerations		

13.1 Waste treatment methods

General information:	Avoid discharges to atmosphere. Consult supplier for specific recommendations. Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Disposal methods:	Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

SECTION 14: Transport information

ADR

14.1 UN Number:	UN 1950
14.2 UN Proper Shipping Name:	AEROSOLS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.2
Hazard No. (ADR):	-
Tunnel restriction code:	(E)
SDS_DK - 000010059150	



SAFETY DATA SHEET TL4 Leak detecting spray

		5 1
Issue Date:	13.10.2020	Version: 1.0
Last revised date:	23.10.2020	

SDS No.: 000010059150 18/21

	14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user:	– Not applicable –
RID		
	 14.1 UN Number: 14.2 UN Proper Shipping Name 14.3 Transport Hazard Class(es) Class: Label(s): 14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user: 	UN 1950 AEROSOLS 2 2.2 - Not applicable -
IMDO	 14.1 UN Number: 14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es) Class: Label(s): EmS No.: 14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user: 	UN 1950 AEROSOLS 2.2 2.2 F-D, S-U – Not applicable –
ΙΑΤΑ	 14.1 UN Number: 14.2 Proper Shipping Name: 14.3 Transport Hazard Class(es): Class: Label(s): 14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user: Other information Passenger and cargo aircraft: Cargo aircraft only: 	UN 1950 Aerosols, non-flammable 2.2 2.2 - Not applicable - Allowed. Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable



TL4 Leak detecting spray

Issue Date:	13.10.2020	Version: 1.0	SDS No.: 000010059150
Last revised date:	23.10.2020		19/21

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:

Classification	Lower-tier	Upper-tier
	Requirements	Requirements
P5c. Flammable liquids	5.000 t	50.000 t

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
2-Amino-2-methylpropanol	124-68-5	0,1 - 1,0%
1,2-Benzisothiazol-3(2H)-one	2634-33-5	0 - <0,1%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives. This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830. **15.2 Chemical safety assessment:** No Chemical Safety Assessment has been carried out. **SECTION 16: Other information**

Revision Information:

Not relevant.



TL4 Leak detecting spray

Issue Date:	13.10.2020	Version: 1.0	SDS No.: 000010059150
Last revised date:	23.10.2020		20/21

K	
Key literature references and sources for data:	Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:
	Agency for Toxic Substances and Diseases Registry (ATSDR)
	(http://www.atsdr.cdc.gov/).
	European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
	European Chemical Agency: Information on Registered Substances
	http://apps.echa.europa.eu/registered/registered-sub.aspx#search
	European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling quide", as amended.
	International Programme on Chemical Safety (http://www.inchem.org/)
	ISO 10156:2010 Gases and gas mixtures $$ - Determination of fire potential and
	oxidizing ability for the selection of cylinder valve outlets.
	Matheson Gas Data Book, 7th Edition.
	National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
	The ESIS (European chemical Substances 5 Information System) platform of the
	former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).
	The European Chemical Industry Council (CEFIC) ERICards.
	United States of America's National Library of Medicine's toxicology data network
	TOXNET (http://toxnet.nlm.nih.gov/index.html)
	Threshold Limit Values (TLV) from the American Conference of Governmental
	Industrial Hygienists (ACGIH).
	Substance specific information from suppliers. Details given in this document are believed to be correct at the time of publication.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 as amended.	Classification procedure
Aerosols, Category 3	On basis of test data
Serious eye irritation, Category 2	On basis of test data

Wording of the H-statements in section 2 and 3

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.



TL4 Leak detecting spray

Issue Date:	
Last revised date:	

13.10.2020 23.10.2020 Version: 1.0

SDS No.: 000010059150 21/21

Training information:	Users of breathing apparatus must be trained. Ensure operators understand the hazards.
Classification according to Regulat	ion (EC) No 1272/2008 as amended.
	Aerosol 3, H229
	Eye Irrit. 2, H319
Other information:	Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.
Last revised date: Disclaimer:	23.10.2020 This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.